


# CHICAGO FAUCETS

Last As Long As The Building



2100 SOUTH CLEARWATER DRIVE  
DES PLAINES, ILLINOIS 60018-5999

FITTING NO.

745-VO

SUBMITTED MODEL NO.

JOB NAME

ITEM NO.

SUBMITTED AS SHOWN

SUBMITTED AS NOTED

SEE ATTACHED FOR  
SUBMITTED MODIFICATION

## MOUNTING HOLE DETAIL

3-1/2" [89mm]

13/16" [21mm]

4-1/4" [108mm]

9/32 [7mm]  
DIA. HOLES  
(3 PLACES)

ROTATING  
KNEE PEDAL

FRONT OF  
LAVATORY

9-1/4" [235mm]

5" [127mm]

1/2" NPT FEMALE  
THREAD INLET

AS REQUIRED

ADJUSTABLE  
SCREW

2-1/2" [64mm]

6" [152mm]  
SUGGESTED

6-5/8" [168mm]

13" [330mm]

11-1/2" [292mm]

NOTE: ALL DOTTED LINE PIPING IS  
1/2" NPT AND SUPPLIED BY OTHERS

1-11/16" [43mm]

1/2" [13mm]

2-1/2" [64mm]  
DIA. FLANGE

3/8" NPT FEMALE  
THREAD OUTLET

24" [610mm] FROM  
FLOOR (SUGGESTED)

5/8" [16mm]

2-5/8" [67mm]

SEE MOUNTING  
HOLE DETAIL

#14 ROUND HEAD  
BRASS SCREW  
2" [51mm] LONG

DIMENSIONS IN INCHES AND [MILLIMETERS].

### TECHNICAL DATA

- KNEE ACTION PEDAL VALVE WITH WALL BRACKET
- 699 STRAIGHT INLET SERVICE STOPS WITH LOOSE KEY
- NAIAD SELF CLOSING CARTRIDGES
- FINISH: CHROME PLATE

- 1021 STEDI FLOW CONTROLS
- 1.6 GPM [6 L/min.] FLOW RATE
- ASME A112.18.1M COMPLIANT
- CSA B125 COMPLIANT

DATE: 05-03-02

BY: SID

CHK'D:

APP'D:

REV: A

745-VO

IS ASSUMED FOR USE OF SUPERCEDED OR VOIDED DATA.

ROUGHING IN DIMENSIONS MAY VARY AND ARE SUBJECT TO CHANGE. NO RESPONSIBILITY