

Features

- Quarter-turn washerless ceramic disc valves
- 11-13/16" (300 mm) swing spout reach
- Matching finish side sprayer
- Lower flow aerator options are available
- 1.5 gpm (5.7 lpm) maximum flow rate at 60 psi (4.14 bar)

Material

- Brass
- Brass valve bodies

Installation

- Flexible connections for easy installation

Recommended Products/Accessories

K-23723 Faucet cleaner

Optional Products/Accessories

1095353 DEEP ROUGH-IN KIT, VOS AND SIDESPRAY

1054432 1.5 GPM (5.7 l/min) Aerator Kit



ADA

CSA B651

OBC

Codes/Standards

ASME A112.18.1/CSA B125.1

All applicable US Federal and State material regulations

DOE - Energy Policy Act 1992

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

OBC

IAPMO Certification

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.



Sidespray:

Pressure: 60 psi (4.1 bar)

Spout:

Spout reach: 11-13/16" (300 mm)

Install this product according to the installation guide.

Lower flow or higher flow aerator options are available. Please refer to the KOHLER Price Book.

ADA complaint for faucet handles only.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.