## **KOHLER**<sub>®</sub>

## Levity® Frameless Sliding Shower Door K-706014-D3

## Features

- Innovative roller design simplifies installation and provides out-of-plumb adjustability while glass is installed.
- Cushioned center guide provides smooth, quiet sliding action.
- Gently curved towel bars, inside and outside, provide integrated storage on the door.
- CleanCoat<sup>®</sup> technology creates a protective barrier that repels water, prevents dirt and minerals from collecting, and makes it easier to remove hard water spots.

## Technology

• Frameless, 1/4-inch-thick Frosted tempered glass.

## Installation

- Sliding shower door.
- Not for use in hospitality.

#### Recommended Products/Accessories K-23723 Faucet cleaner

## **Included Components**

Additional Components: Hardware kit



## **Codes/Standards**

CPSC 16CFR 1201 ANSI Z97.1

## KOHLER<sup>®</sup> One-Year Limited Warranty

See website for detailed warranty information.

## **Available Colors/Finishes**

Color tiles intended for reference only.

# Color Code Description Image: SH Bright Silver Image: MX Matte Nickel

- ABV Anodized Brushed Bronze
- ABZ Anodized Dark Bronze
- BL Matte Black

## **Available Glass Options**

Code Description

D3 Frosted





## Levity® Frameless Sliding Shower Door K-706014-D3



## **Technical Information**

All product dimensions are nominal.

P	
Installation type:	For shower base installation
Opening style:	Sliding/Bypass
Opening Width - Min:	44-5/8" (1133 mm)
Opening Width - Max:	47-5/8" (1210 mm)
Walk-through - Min:	18-1/16" (459 mm)
Walk-through - Max:	21-1/16" (535 mm)
Base-To-Wall Radius – Max:	1/2" (13 mm)
Glass thickness:	1/4" (6 mm)
Glass coating:	CleanCoat®

### Notes

Install this product according to the installation guide.

If replacing a shower door, the narrow wall jamb design of this door may not cover the existing shower door holes.

The vertical opening should be a minimum of 76-1/2" (1943 mm) to allow for installation clearance.

