

### Features

- Fixture and touchless flushometer combination is engineered for optimal performance
- Washout urinal
- 1 pint or 0.125 gpf (0.47 lpf)
- 3/4" (19 mm) top spud
- Flush valve activation distance is factory-set
- No external flush volume adjustment ensures water conservation
- 24-hour automatic sentinel flush keeps trapway fresh
- Mechanical override enables flushometer to be used manually even during a power outage
- Chloramine and chlorine resistance on all rubber components exposed to waterway
- Locking stop cap provides protection against vandalism
- 125-micron filter protects internal components
- High back pressure vacuum breaker
- Powered by 1.5V AA lithium batteries
- For this combination, order K-20713-ET urinal and K-10UD00D20 flushometer
- This product can help a building earn Water Efficiency points in LEED® Green Building Rating System

### Material

- Vitreous china urinal
- Brass flush valve with durable Polished Chrome finish

### Technology

- Electronic infrared sensor with Tripoint® technology for accurate activation
- Patented piston technology for superior flush volume accuracy



ADA


### Codes/Standards

ASME A112.18.1/CSA B125.1  
ASME A112.19.2/CSA B45.1  
ASSE 1037/ASME A112.1037/CSA B125.37  
DOE - Energy Policy Act 1992  
EPA WaterSense®  
California Energy Commission (CEC)  
ADA  
ICC/ANSI A117.1  
IAPMO Certification

### KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

**Note:** Customer Connection Pipe must have 2 NPT External Thread.



### Technical Information

All product dimensions are nominal.

Spud size: 3/4, Outlet, Top  
Max. Water per Flush: 0.125 gal (0.5 L)

### Pressure and Supply Requirements

Fixture pressure min (static): 25 psi (172.4 kPa)  
Fixture flow rate min: 25 gpm (94.6 lpm)  
Fixture pressure max (static): 80 psi (551.6 kPa)

### Notes

Install this product according to the installation instructions.

ADA compliant when installed to the specific requirements of these regulations.